

CONSOLIDECK®
HIGH PERFORMANCE CONCRETE

LSKlean

maintenance cleaner for lithium silicate hardened & densified concrete floors

OVERVIEW

Consolideck® LSKlean is a concentrated maintenance cleaner for concrete floors treated with Consolideck® lithium silicate hardening and densifying products.

The specialized blend of degreasers and detergents removes most common soiling found on concrete floors. It is perfect for use on concrete floors everywhere, from warehouses and manufacturing plants to schools, stores, hospitals and restaurants.

LSKlean contains a lithium silicate hardener-densifier. The lithium silicate component helps maintain concrete hardness by curing any "soft" calcium hydroxide left over from the original hardening-densifying treatment.

Though LSKlean was specifically designed for lithium silicate hardened and densified floors, it is an effective maintenance cleaner for almost any concrete floor. It's also ideal for cleaning polished concrete counter tops

Regular cleaning with LSKlean ensures the highest appearance and performance standards for all indoor concrete flatwork.

SPECIFICATIONS

For all PROSOCO product specifications visit www.prosoco.com and click on "SpecBuilder" or "Solution Finder."

ADVANTAGES

- Maintains concrete floor hardness and shine.
- Removes most common soiling.
- Flexible dilution for both surface and deep cleaning.
- Concentrated for economy of storage and transport.
- No rinsing needed for routine surface cleaning of floors.
- Great for polished concrete counter tops.

Limitations

- May not remove some embedded stains.

REGULATORY COMPLIANCE

VOC Compliance

Consolideck® LSKlean is compliant with all national, state and district VOC regulations.

TYPICAL TECHNICAL DATA

FORM	clear liquid, soapy odor
SPECIFIC GRAVITY	1.00
pH	9.87
WT/GAL	8.38 lbs
ACTIVE CONTENT	NA
TOTAL SOLIDS	NA
VOC CONTENT	4% maximum
FLASH POINT	>200°F (>93°C) ASTM D 3278
FREEZE POINT	NA
SHELF LIFE	2 years in unopened, factory-sealed container

PREPARATION

Sweep or vacuum to remove loose materials from the surface to be cleaned. Pre-clean oil spots or other deep stains with the appropriate Consolideck® product.

Surface and Air Temperatures

Cleaning effectiveness is reduced when surface and air temperatures fall below 50°F (10°C). Do not apply at temperatures below 40°F (4°C).

Equipment

Apply to concrete floors using a mop or automatic scrubber.

Apply to concrete counter tops using a sponge or clean cloth.

Storage and Handling

Store in a cool, dry place away from other chemicals. Keep tightly closed when not dispensing. Do not alter or mix with other chemicals.

Published shelf life assumes upright storage of factory sealed containers in a dry place. Maintain temperatures of 45-100°F (7-38°C). Do not double stack pallets.

Dispose of unused product and container in accordance with local, state and federal regulations.

APPLICATION

Before use, read "Preparation" and "Safety Information."

ALWAYS TEST each type of surface and coating for suitability and results before overall application. Test using the following application instructions. Let test area dry thoroughly before inspection.

Dilution & Coverage

For normal cleaning

dilute 4 oz of cleaner per gallon of fresh water

For deep cleaning

dilute 8 oz of cleaner per gallon of fresh water

One gallon of cleaner concentrate yields 33-gallons of ready-to-use product.

Application Instructions

Concrete Floors

1. Apply with a mop or automatic scrubber.
2. Rinsing is not necessary for routine surface cleaning of concrete floors. Just mop up spent cleaner and dissolved contaminants, or let the automatic scrubber vacuum it up.
3. After deep-cleaning, rinse well with fresh water. Do not let the cleaner dry on the floor.
4. Buff the cleaned floor with a white pad to increase the shine.

ALWAYS TEST

ALWAYS TEST a small area of each surface to confirm suitability and desired results before starting overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application.

Application Instructions

Concrete Counter Tops

1. Gently scrub-apply with sponge or clean cloth.
2. Thoroughly wipe down counter tops with fresh water after cleaning.

Cleanup

Clean tools and equipment using fresh water.

SAFETY INFORMATION

Consolideck® LSKlean is a concentrated cleaner and may cause irritation. Use appropriate safety equipment and job site controls during application. Read full label and MSDS for precautionary instructions before use.

First Aid

Ingestion: Do not induce vomiting. Get immediate medical assistance.

Eye Contact: Rinse thoroughly for 15 minutes. Get medical assistance.

Skin Contact: Rinse thoroughly. Get medical attention if irritation persists.

Inhalation: Remove to fresh air. Get medical attention as necessary.

24-Hour Emergency Information:
INFOTRAC at 800-535-5053

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care - technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com, for the name of the Consolideck® representative in your area.

BEST PRACTICES

For spot-cleaning heavily soiled areas, begin testing LSKlean at a dilution of 8-ounces of cleaner to one gallon fresh water.

Do not use dilutions stronger than one part product to three parts water. Always use the mildest effective dilution possible.

Thoroughly rinse deep-cleaned or spot-cleaned floors where dilutions stronger than 4-ounces per gallon are used.

Always use plenty of clean water for wipe-down rinsing after cleaning concrete counter tops.

To remove deeply embedded oil and grease stains, test Consolideck® Oil & Grease Stain Remover.

Never go it alone. If you have problems or questions, contact your local PROSOCO distributor or field representative. Or call PROSOCO technical Customer Care, toll-free, at 800-255-4255.