IAVINA



L3213REUB REMOTE-CONTROLLED


Technical Data

Motor Power	15 KW
Voltage (50/60 Hz)	3ph x 380-400V
Amperage	32 Amp
Dedicated Breaker Requirement	32 Amp
Recommended dust extractor - V32EU	
Weight of Machine	729 kg
Adjustable Grinding Pressure, Integrated weights with 4 positions	250.5-389.5 kg
Attachment Speed	400-650 rpm
Working Width	814 mm
Tool Holder Diameter	3x335 mm
Vacuum Hose Port	Camlock E300
Water feeding (from tank or hose connection)	Under machine
Water tank capacity	46L
Cable Length	57 ft / 17.4 m
AMG Battery RC Battery (rechargeable)	12 V/2x7 AH AA 1.2V
Machine Size LxWxH	246x86x130 cm
Crate size LxWxH	160x95x160 cm









NEW INTELLIGENT REMOTE CONTROL FOR PRECISE CONTROL OVER THE MACHINE.

INTUITIVE TOUCHSCREEN HMI PROVIDES ESSENTIAL OPERATING INFORMATION AND IMPLEMENTS OPERATOR'S INSTRUCTIONS.

GRINDER CAN BE USED IN 3 MODES:
REMOTE-CONTROLLED, SELF-PROPELLED AND MANUAL.

L3213RE

- DUST-PROOF PLANETARY DRIVE
- 3X335MM GRINDING HEADS WITH COUNTER-CLOCKWISE ROTATION. USE THE BLUE PCD'S AND CARBIDE SCRAPERS.
- NEW & IMPROVED WATER SYSTEM WITH 2 VALVES FOR USING WATER FROM TANK OR EXTERNAL SOURCE
- ADDED PROTECTION AGAINST EXCESSIVE VOLTAGE
- EASY-TO-USE INTEGRATED WEIGHTS
- IMPROVED DUST COLLECTION EFFICIENCY
- LED LIGHTS IN FRONT & BACK
- NEW ADJUSTABLE HANDLE BAR
- CHARGING PHONE STATION WITH USB
- A DURABLE STAINLESS STEEL CUP HOLDER
- HEAVY-DUTY THIRD WHEEL AND LARGE SOLID RUBBER TIRES



